

Resurge Failsafe System

P.O. Box 984 - Windham, ME 04062

Phone: 1 (207) 939-8112

Email: tpage@resurgefailsafe.com

Web: www.resurgefailsafe.com

Failsafe-Electric Valve actuator power supply Specification Sheet

To avoid confusion when ordering or inquiring about **Resurge 1620ESv2 Series** Failsafe-Electric actuators use the form below. *Please note **ALL** information must be filled in, no other form will be accepted when ordering Electric Failsafe actuators.*

		DATE:
Company Name:		Contact Name:
E-mail:		<input type="checkbox"/> E-mail Quote
Address:		
City:	State:	Zip:
Phone:	Ext:	Fax:

Actuator Model Number:	First Actuator:	Second Actuator:	
Actuator FLA Full Load Amps:	First Actuator: _____Amps.	Second Actuator: _____Amps.	
Actuator LRA Lock Rotor Amps:	First Actuator: _____Amps.	Second Actuator: _____Amps.	
Number of Actuators per Failsafe: (check one)	<input type="checkbox"/> One Actuator <input type="checkbox"/> Two Actuators	<input type="checkbox"/> Actuators are Sequential <input type="checkbox"/> Actuators are Simultaneous	
Length of time to close Each Valve in seconds:	First Valve: _____sec.	Second Valve: _____sec.	
Enclosure NEMA Type Required (check one)	<input type="checkbox"/> NEMA 4 <input type="checkbox"/> NEMA 4X (Stainless Steel) <input type="checkbox"/> NEMA 4X (Fiberglass)	<input type="checkbox"/> NEMA 6P <input type="checkbox"/> NEMA 7 (Explosion Proof) <input type="checkbox"/> NEMA 12	<input type="checkbox"/> Other: _____
System Running Voltage (check one)	<input type="checkbox"/> _____ <input type="checkbox"/> 120 Volts	<input type="checkbox"/> 220Volts 50Hz	<input type="checkbox"/> _____
Actuator Service Type:	<input type="checkbox"/> Modulating <input type="checkbox"/> Non-Modulating	<input type="checkbox"/> Requires a Heater <input type="checkbox"/> Requires a Fan	

Note any special requirements here:

EmailBack to: tpage@resurgefailsafe.com

Rev: 0623